

MONACO COMPONENTS, INC.

EXTERNAL DRIVE STYLE PCB MOUNTING



**4000
series**

- Compact design.
- Three pins for PCB mounting.

MODEL	MPB-4304	MPF-4315
RESONANT FREQUENCY	2100 Hz \pm 500 Hz	3600 Hz
OPERATING VOLTAGE	30 V _{p-p} MAX.	40 V _{p-p} MAX.
RATED VOLTAGE	10 V _{p-p} SQUAREWAVE	9 V _{p-p} SQUAREWAVE
CAPACITANCE	25000 \pm 30% pF	25000 \pm 30% pF @ 120 Hz
DRIVE CIRCUIT	EXTERNAL	EXTERNAL
SOUND PRESSURE *	90 dB MIN. @ 10 cm @ 2100 Hz	80 dBA MIN. @ 10 cm @ 3600 Hz
CURRENT CONSUMPTION *	10 mA MAX.	3 mA MAX.
tone	DEPENDENT ON DRIVE CIRCUIT USED	DEPENDENT ON DRIVE CIRCUIT USED
CONNECTION STYLE	PCB MOUNT (PINS)	PCB MOUNT (PINS)
OPERATING TEMPERATURE	-20° to +60° C	-20° to +85° C



* VALUES AT RATED VOLTAGE

MPB-4304



MPF-4315

COLOR : GREY
SEALED AND WASHABLE
PBT HOUSING MATERIAL



ALL DIMENSIONS IN mm

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTIFICATION / MODELS SHOWN SUBJECT TO LIMITED WARRANTY

SALES OFFICE (516)-767-6644

CORPORATE OFFICE

P.O. Box 575, Scotch Plains, NJ. 07076

Phone: (908)-322-2977 Fax: (908)-322-2358

E-mail: info@monacocomponents.com

www.monacocomponents.com